



MIDILED

Compact, space-saving, strong on the surface

The MIDILED is the right choice if a strong, flat illumination is required, but where the working area at the machine offers very little space. The LED luminaire provides daylight white illumination in the machine room. It can be attached via the stainless steel mounting bracket and its inclination can be adjusted.

The Technology

- Crack-resistant TSG 4 mm
- Heat dissipation via rear aluminium base body
- IP68 degree of protection

Your benefits


- Strong surface illumination, flicker-free without UV and IR component
- Very compact (total length: 148 mm)
- Simple upgrading or retrofitting in machine tools
- Chip bombardment-proof and oil-resistant

Areas of application

- for machines or working environments with very little space
- Lathes, drilling, milling and grinding machines

Design

- Very compact LED luminaire for fixture using the mounting bracket made of stainless steel, adjustable at an angle of $\pm 30^\circ$



MIDILED, 5200–5700K	Product no.	Optics	E _{average} *	E _{max} *	Luminous flux	Output	Connection
MIDILED	110614-01	120°	181 lx	248 lx	approx. 609 lm	7 W	24V DC

Incl. V2A mounting bracket for pivotable mounting
Power supply units and connection material see Accessories

* Average and maximum lighting intensities, measurement area 100 cm x 100 cm at 100 cm distance

